

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ceramic-Polymer STP-ep Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coatings and paints, fillers, putties, thinners

Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Polypropyleneglycol-Epichlorhydrine-Copolymer

Signal word: Warning

Safety Data Sheet


according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 2 of 13

Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	25 -< 50 %
	701-263-0	
		01-2119454392-40
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	5-7 %
	618-939-5	
		01-2119463471-41
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412	
9072-62-2	Polypropyleneglycol-Epichlorhydrine-Copolymer	1-5 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 3 of 13

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately.
Do not wash with: Solvents/Thinner

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.
After contact with skin, wash immediately with plenty of Lutrol.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO₂). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.
Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.
Provide adequate ventilation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 4 of 13

Personal protection equipment: see section 8

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8. Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

Keep away from:

Food and feedingstuffs

Oxidising agent

Further information on storage conditions

Keep away from:

Frost

Heat

Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
	Worker DNEL, long-term	inhalation	systemic	29,39 mg/m ³
	Worker DNEL, long-term	dermal	systemic	104,15 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	0,0083 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	8,7 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	62,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	6,25 mg/kg bw/day
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)			
	Worker DNEL, long-term	inhalation	systemic	10,57 mg/m ³
	Worker DNEL, acute	inhalation	systemic	10,57 mg/m ³
	Worker DNEL, long-term	inhalation	local	0,44 mg/m ³
	Worker DNEL, long-term	dermal	systemic	6 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	5,29 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	5,29 mg/m ³
	Consumer DNEL, long-term	inhalation	local	0,27 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	3 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	1,7 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	1,5 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	1,5 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 6 of 13

PNEC values

CAS No	Substance	Value
	Environmental compartment	
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
	Freshwater	0,003 mg/l
	Freshwater sediment	0,294 mg/kg
	Marine sediment	0,029 mg/kg
	Soil	0,237 mg/kg
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	
	Freshwater	0,011 mg/l
	Freshwater (intermittent releases)	0,115 mg/l
	Marine water	0,001 mg/l
	Freshwater sediment	0,283 mg/kg
	Marine sediment	0,028 mg/kg
	Micro-organisms in sewage treatment plants (STP)	1 mg/l
	Soil	0,223 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Eye/face protection

Suitable eye protection:

Eye glasses with side protection
goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Wearing time with permanent contact: Thickness of the glove material: $\geq 0,4$ mm, Breakthrough time (maximum wearing time): >480 min

Wearing time with occasional contact (splashes):: Thickness of the glove material: $\geq 0,1$ mm, Breakthrough time (maximum wearing time) > 30 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

Protective clothing

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 7 of 13

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	various	
Odour:	characteristic	
pH-Value:		No data available

Changes in the physical state

Melting point:		No data available
Initial boiling point and boiling range:		No data available
Sublimation point:		No data available
Softening point:		No data available
Pour point:		No data available
Flash point:		>65 °C

Flammability

Solid:		No data available
Gas:		No data available

Explosive properties

No information available.

Lower explosion limits:		No data available
Upper explosion limits:		No data available
Ignition temperature:		No data available

Auto-ignition temperature

Solid:		No data available
Gas:		No data available

Decomposition temperature:		No data available
----------------------------	--	-------------------

Oxidizing properties

No information available.

Vapour pressure:		No data available
Density:		~1,75 g/cm ³
Water solubility:		No data available

Solubility in other solvents

No information available.

Partition coefficient:		No data available
------------------------	--	-------------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 8 of 13

Viscosity / dynamic: ~8000 mPa·s

Vapour density: No data available

Evaporation rate: No data available

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

Does not decompose when used for intended uses. No known hazardous decomposition products.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Acid, Oxidising agent

10.6. Hazardous decomposition products

Does not decompose when used for intended uses. No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)				
	oral	LD50 mg/kg	3010 Rat	Study report (1981)	OECD Guideline 401

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane; Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2); Polypropyleneglycol-Epichlorhydrine-Copolymer)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 9 of 13

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)					
	Acute fish toxicity	LC50 mg/l	ca. 30	96 h	Oncorhynchus mykiss	Study report (1990) OECD Guideline 203
	Acute crustacea toxicity	EC50 ca. 57 mg/l	ca. 39 -	48 h	Daphnia magna	Study report (1989) OECD Guideline 202

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	ca. 0,822

BCF

CAS No	Chemical name	BCF	Species	Source
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	3,57		Publication (2009)

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 10 of 13

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-

Inland waterways transport (ADN)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	274, 335, 969
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-F

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 11 of 13

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	A97 A158 A197
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y964
Excepted quantity:	E1
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	epoxy resin

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 12 of 13

(European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
 (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself.
 No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose.
 The user must make their own determination as to suitability.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ceramic-Polymer STP-ep Part A

Revision date: 06.12.2019

Page 13 of 13

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)