

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Proguard CN-1M V12 H3 Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coatings and paints, fillers, putties, thinners

Uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	DE-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1C

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Germ cell mutagenicity: Muta. 2

Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May damage fertility.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 2 of 15

Hazard components for labelling

Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Phenol, polymer with formaldehyde, glycidether

Signal word: Danger

Pictograms:



Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H360F May damage fertility.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 3 of 15

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane	25-30 %
	701-135-4	01-2120078341-60
	Muta. 2, Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 2; H341 H360F H314 H318 H317 H411	
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	25 - 30 %
	701-263-0	01-2119454392-40
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
28064-14-4	Phenol, polymer with formaldehyde, glycidether	15-20 %
	608-164-0	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
78-93-3	butanone; ethyl methyl ketone	1-5 %
	201-159-0	606-002-00-3
	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately.
Do not wash with: Solvents/Thinner

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 4 of 15

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

After contact with skin, wash immediately with plenty of Lutrol.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO₂). alcohol resistant foam. Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

Provide adequate ventilation.

Personal protection equipment: see section 8

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8. Wear personal protection equipment (refer to section 8). Keep container tightly closed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 5 of 15

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

Keep away from:

Food and feedingstuffs

Oxidising agent

Further information on storage conditions

Keep away from:

Frost

Heat

Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 6 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane			
Worker DNEL, long-term		inhalation	systemic	1,17 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,67 mg/kg bw/day
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
Worker DNEL, long-term		inhalation	systemic	29,39 mg/m ³
Worker DNEL, long-term		dermal	systemic	104,15 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	0,0083 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,25 mg/kg bw/day
28064-14-4	Phenol, polymer with formaldehyde, glycidether			
Worker DNEL,		dermal		104,15 mg/kg bw/day
Worker DNEL,		inhalation		29,39 mg/m ³
78-93-3	butanone; ethyl methyl ketone			
Consumer DNEL, long-term		oral	systemic	31 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	412 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	106 mg/m ³
Worker DNEL, long-term		inhalation	systemic	600 mg/m ³
Worker DNEL, long-term		dermal	systemic	1161 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 7 of 15

PNEC values

CAS No	Substance	Value
	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane	
	Freshwater	0,004 mg/l
	Freshwater (intermittent releases)	0,037 mg/l
	Freshwater sediment	0,02 mg/kg
	Marine sediment	0,002 mg/kg
	Soil	0,002 mg/kg
	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
	Freshwater	0,003 mg/l
	Freshwater sediment	0,294 mg/kg
	Marine sediment	0,029 mg/kg
	Soil	0,237 mg/kg
78-93-3	butanone; ethyl methyl ketone	
	Freshwater	55,8 mg/l
	Freshwater (intermittent releases)	55,8 mg/l
	Marine water	55,8 mg/l
	Freshwater sediment	284,74 mg/kg
	Marine sediment	284,7 mg/kg
	Secondary poisoning	1000 mg/kg
	Micro-organisms in sewage treatment plants (STP)	709 mg/l
	Soil	22,5 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Eye/face protection

Suitable eye protection:
Eye glasses with side protection
goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 8 of 15

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Wearing time with permanent contact: Thickness of the glove material: $\geq 0,4$ mm, Breakthrough time (maximum wearing time): >480 min

Wearing time with occasional contact (splashes):: Thickness of the glove material: $\geq 0,1$ mm, Breakthrough time (maximum wearing time) > 30 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Breakthrough times and swelling properties of the material must be taken into consideration.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device (EN 14387) A-P3

Self-contained respirator (breathing apparatus) (DIN EN 133)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: black
Odour: characteristic

pH-Value: No data available

Changes in the physical state

Melting point: No data available

Initial boiling point and boiling range: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Flash point: > 100 °C

Flammability

Solid: No data available

Gas: No data available

Explosive properties

No information available.

Lower explosion limits: No data available

Upper explosion limits: No data available

Ignition temperature: No data available

Auto-ignition temperature

Solid: No data available

Gas: No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 9 of 15

Decomposition temperature: No data available

Oxidizing properties

No information available.

Vapour pressure: No data available

Density (at 20 °C): ~1,3 g/cm³

Water solubility: No data available

Solubility in other solvents

No information available.

Partition coefficient: No data available

Viscosity / dynamic: No data available

Vapour density: No data available

Evaporation rate: No data available

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid, Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Acid, Oxidising agent

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane				
	oral	LD50 3398 mg/kg	Rat	Other company data (1976)	OECD Guideline 401
	dermal	LD50 > 3170 mg/kg	Rat	Study report (1976)	OECD Guideline 402
28064-14-4	Phenol, polymer with formaldehyde, glycidether				
	oral	LD50 >2000 mg/kg	Rat	Supplier	
	dermal	LD50 >2000 mg/kg	Rabbit	Supplier	
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 >2000 mg/kg	Rat	Supplier	OECD 423
	dermal	LD50 6400 - 8000 mg/kg	Rabbit	Supplier	
	inhalation (4 h) aerosol	LC50 34,5 mg/l	Rat		

Irritation and corrosivity

Causes severe skin burns and eye damage.
Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane; Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane; Phenol, polymer with formaldehyde, glycidether)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)
May damage fertility. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)
Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 11 of 15

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane					
	Acute fish toxicity	LC50 75 mg/l	96 h	Cyprinus carpio	Study report (1996)	OECD Guideline 203
	Acute algae toxicity	ErC50 9 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2014)	OECD Guideline 201
	Acute crustacea toxicity	EC50 3,7 mg/l	48 h	Daphnia magna	Study report (2015)	OECD Guideline 202
28064-14-4	Phenol, polymer with formaldehyde, glycidether					
	Acute fish toxicity	LC50 2,54 mg/l	96 h	Leuciscus idus (golden orfe)	Supplier	
	Acute crustacea toxicity	EC50 2,55 mg/l	48 h	Daphnia magna (Big water flea)	Supplier	
78-93-3	butanone; ethyl methyl ketone					
	Acute fish toxicity	LC50 2993 mg/l	96 h	Pimephales promelas	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 2029 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 308 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Acute bacteria toxicity	(1150 mg/l)		Pseudomonas putida	Supplier	

12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
78-93-3	butanone; ethyl methyl ketone			
	OECD 301	98%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane	2,93 - 2530
78-93-3	butanone; ethyl methyl ketone	0,3

12.4. Mobility in soil

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 12 of 15

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1760
<u>14.2. UN proper shipping name:</u>	CORROSIVE LIQUID, N.O.S. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Classification code:	C9
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1760
<u>14.2. UN proper shipping name:</u>	CORROSIVE LIQUID, N.O.S. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	III
Hazard label:	8
Classification code:	C9
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 13 of 15

14.1. UN number:	UN 1760
14.2. UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Marine pollutant:	P
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B
Segregation group:	alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1760
14.2. UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	yes
Danger releasing substance:	epoxy resin

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 14 of 15

Information according to 2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D):

2 - clearly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl)-2-hydroxy butane

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane butanone; ethyl methyl ketone

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international conernat le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Proguard CN-1M V12 H3 Part A

Revision date: 06.12.2019

Page 15 of 15

BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1C; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)